# MODEL MINI-1 GLYCOL CIRCULATOR PERFECTION





### LINE RUNS

- Up to 100 feet
- Multiple dispensing locations

#### **CONSTANT RUNNING COMPRESSOR**

- Longer compressor life
- Self-Starting after power failure

#### Perfection Equipment, Inc. Perfecta Stainless Division

#### **REFRIGERATION SYSTEM**


Includes a 1/3 horsepower continuous running compressor. An externally equalized thermostatic expansion valve (TXV) controls the flow of liquid refrigerant into the evaporator. A hot gas bypass valve (HGB) controls the refrigerant affect and adjusts the unit's horsepower to the load.

#### **COOLANT SYSTEM**

The Coolant System consists of a water/glycol mixture of 2/1 with a reservoir tank incorporated within the unit to hold a small percentage of coolant. A 60 GPH brass pump draws the coolant from the bottom of the tank and propels it into the chiller coil. The coolant exits the coil and goes directly to the line run. Upon return from the line run the coolant goes directly to the reservoir tank completing the cycle.

## SERVICE AND INSTALLATION

Available from a national network of trained and authorized technicians.



## MODEL MINI-1 GLYCOL CIRCULATOR



#### Perfection Equipment, Inc. Perfecta Stainless Division

# <u>MODEL MINI-1</u> <u>AVAILABLE IN AIR-COOLED</u> <u>115V</u>

	THE UNIT(S	I: REQUIRED VENTILATION P ) ARE LOCATED <b>DOES NOT E</b> IT(S) BASED ON BTU'S FOR T	EXCEED 85°F. SIZE	VENTILATION SYS		
1/3 H.P. MINI-1		GLYCOL CHILLER		HEAT OF REJECTION 3802 BTU / HR		
ELECTRICAL: DEDICATE	O CIRCUIT(S)	FOR EACH UNIT (S) TO BE P	ROVIDED BY OTHE	RS BASED ON THE	MODEL BELOW:	
1/3 H.P. MINI-1	115V	AIR- COOLED	60 HZ, SINGL	E PHSE 20.0 AMP	RLA 5.8 MCA 13	
HIPPING DIMENSIONS:	30" X 17" X	13"				
HIPPING WEIGHT: 90 lbs	S.					
7/8" ACCESS HOLE FOR HARDWIRE ELECTRICAL CONNECTION	AIR FLOW		AIR	FLOW		
15"-		27-3/4" - FRONT VIEW	•		15"	

PERFECTION Equipment, Inc. 4259 Lee Avenue, Gumee, Illinois 60031, Phone: 847-244-7200, Fax: 847-244-7205, Toll Free: 800-356-6301 Website: www.perfectequip.com Mail to: sales@perfectequip.com

